



Explosion Proof Peristaltic Pump

Model No.: EXP600-1/YZ35(Aluminum Alloy)

Flow Rate: 414-12000mL/min



Product Features

- JDiven by explosion-proof motor, the power is strong.
- Stepless speed regulation, reversible inversion.
- IP rate: IP55, Explosion-proof grade:ExdIIBT4 Gb
- Suitable for inflammable and explosive industrial sites.

Pump Head



YZ35(Aluminum Alloy)



YZ35(Aluminum Alloy)

Drive	Speed(rpm)	Pump Head	Tube Size	Flow Rate (mL/min)
EXP600-1/YZ35 (Aluminum Alloy)	600	YZ35(Aluminum Alloy)	26#, 73#, 82#	1242-12000

Technical Specifications

Speed range	Manual control: 180-600 rpm; Frequency converter control: 60-600rpm
Speed control	Manual stepless speed regulation/Inverter speed regulation
Voltage	3 phase 380V(standard)/3 phase 220V(optional)
Condition temperature	0-40°C
Relative humidity	<80%
Explosion-proof grade	ExdIIBT4 Gb,ExdIICT4
IP rate	IP55
Drive weight	30kg
Drive dimension(L xWxH)	424 x230x330(mm)



■ Dimension Drawing(Unit:mm)

